



Product Code . DS-FHASC-10122

Fume Hood

Description

Fume Hood

Description:

Fume Hood is used to protect lab environment and operator during general chemical applications. It actively protects operator from inhaling toxic vapors and dramatically reduces the risk of fire and explosion. By installing proper filter, it can also protect environment.

Advantages:

1. Made of porcelain white PP, resistant to strong acid, alkali and anti-corrosion.
2. Microprocessor control system, LED display
3. With memory function in case of power-failure
4. It is safer to use anti-corrosive water tap.
5. Front window which is made of thick transparent toughened glass maximize light and visibility inside the fume hood, providing a bright and open working environment.

Specifications:

External Size (W*D*H)		1040*750*2200 mm	1240*800*2200 mm	1540*800*2200 mm	1840*800*2200 mm
Internal Size (W*D*H)		820*520*872mm	1020*570*872m m	1320*570*872m m	1620*570*872 mm
Work Surface Height		740mm			
Max Opening		815mm			
Air Velocity		0.4~0.6m/s			
Noise		≤60dB			
Illuminating Lamp		LED lamp	Fluorescent Lamp	Fluorescent Lamp	Fluorescent Lamp
		12W*1	30W*2	30W*2	30W*2
Blower		Built-in PP centrifugal blower?2 blowers for FH1800(P) only?			
Front Window		Manual, 5mm toughened glass, height adjustable.			
Power Supply		AC220V±10%, 50/60Hz; 110V±10%, 60Hz			
Consumption		330W	360W	360W	360W
Material	Main Body	Made of Porcelain white PP, thickness 8mm, resistant to strong acid, alkali and anti-corrosion			
	Work Table	Chemical resistant phenolic resin			
Gross Weight		160kg	198kg	225kg	259kg

Didac Scientific Pvt. Ltd,
 Martinfield Business Centre, 108 Martinfield, Welwyn Garden City , United Kingdom
 Direct Contact Details ✉ sales@didacscientific.co.uk
 🌐 www.didacscientific.co.uk/