


## **Didac Scientific**





Product Code . DS-FHASC-10125

# Fume Hood DID207

## Description

### Fume Hood DID207

#### Advantages:

- 1. UV Lamp for sterilization.
- 2. Adjustable air speed: 9 levels.
- 3. Motorized front glass window.
- 4. Microprocessor control system, LED display.LED display filter working time.
- 5. With air velocity memory function in case of power failure.
- 6. Back side air compensation, to avoid turbulence in work area.
- 7. Alarm when filter working time 3500 hours.
- 8. 10°slope front ergonomics design, fatigue-free working posture.

9. Transparent side glass windows maximize light and visibility inside the cabinet, providing a bright and open working environment.

| Specifications:  |   |                 |                 |                 |
|------------------|---|-----------------|-----------------|-----------------|
| External Size    | 1000*840*2150mm   | 1200*840*2150mm | 1500*840*2150mm | 1800*840*2150mm |
| (W*D*H)          |   |                 |                 |                 |
| Internal Size    | 880*730*745mm   | 1080*730*745mm  | 1380*730*745mm  | 1680*730*745mm  |
| (W*D*H)          |   |                 |                 |                 |
| Max Opening      | 520mm   |                 |                 |                 |
| Work Surface     | 750mm   |                 |                 |                 |
| Height           |   |                 |                 |                 |
| Blower           | Built-in centrifugal blowers; Speed adjustable with 9 levels        |                 |                 |                 |
| Air Velocity     | 0.3~0.8m/s  |                 |                 |                 |
| Noise            | ?60dB   |                 |                 |                 |
| Fluorescent Lamp | 18W*1   | 18W*1           | 36W*1           | 36W*1           |
| UV Lamp          | Emission of 253.7 nano meters for most efficient decontamination    |                 |                 |                 |
| Front Window     | Motorized;5 mm toughened glass, anti-UV                             |                 |                 |                 |
| Material         | Exterior Body: Cold-rolled steel with anti-bacteria powder coating. |                 |                 |                 |
|                  | Work table: Chemical resistant phenolic resin                       |                 |                 |                 |
| Power Supply     | AC220V±10%, 50/60Hz;100V±10%, 60Hz                                  |                 |                 |                 |
| Consumption      | 400W  | 400W            | 500W            | 500W            |

Didac Scientific Pvt. Ltd,

Martinfield Business Centre, 108 Martinfield, Welwyn Garden City , United Kingdom

Direct Contact Details <sup>™</sup> sales@didacscientific.co.uk

www.didacscientific.co.uk/