

Product Code . DS-DO-10186

Vacuum Drying Oven



Description

Vacuum Drying Oven

Features:

- * PID microprocessor temperature control with LED display.
- * The vacuum is controlled by microprocessor controller with digital display.
- * Vacuum degree is automatically controlled.
- * Silicon rubber sealing ensures the high vacuum degree in the chamber.
- * Polished stainless steel inner chamber.
- * Tempered double-layer glass door ensures the operation safety.
- * The working program can be cycled for 99 times.
- * Inert gas can be filled in the chamber. (Inert gas pressure is not higher than 0.1Mpa when filling in).

Specifications:

Capacity	25L	50L	90L	215L	90 L	215 L
Temp. Range	50~200°C	50~250°C	50~200°C			

Temp. Fluctuation	±1°C					
Vacuum Degree	<133 Pa					
Vacuum Control	/		Automatically; Include one vacuum meter		Automatically; Microprocessor controller with digital display	
Shelves No.	1 pc	2pcs	2 pcs	3 pcs	2 pcs	3 pcs
Power Consumption	500W	1400W	1600W	2200W	1600W	2200W
Power Supply	AC110V/220V±10%,50/60Hz			AC220V±10%, 50/60Hz	AC110V/220V±10%, 50/60Hz	AC220V±10%, 50/60Hz
Internal Size (W*D*H) mm	300*300*280	420*350*370	450*450*450	560*600*640	450*450*450	560*600*640
External Size (W*D*H)mm	580*570*450	710*590*530	660*610*1400	760*720*1670	660*610*1400	760*720*1670
Gross Weight (kg)	50	106	155	195	155	195

Didac Scientific Pvt. Ltd,
 Martinfield Business Centre, 108 Martinfield, Welwyn Garden City , United Kingdom
 Direct Contact Details ✉ sales@didacscientific.co.uk
 🌐 www.didacscientific.co.uk/