

Product Code . DS-I-10192

Constant Temperature and Humidity Incubator

Description

Constant Temperature and Humidity Incubator

Features:

* The working chamber adopt the round angle structure, easy to clean.

* Microprocessor temperature control.

* Double door design and magnetic door sealing.

* Electrical power outlet in the chamber.

* UV light for sterilization.

* LED display for BJPX-HT series, LCD display for BJPX-HTII series.

* The starting up time can be preset.

* Universal Castors for easy movement.

* CFC-free refrigerant with high efficiency.

Safety Function:

• High and low water level alarm. Automatic heating off for low water level.

• Over temperature protection, temperature sensor malfunction alarm.

• Parameters can be saved automatically when power off or system error.

• Notice: Please don't uses in low temperature (?20°C) for long time (?160h).

Specifications:

Capacity	160L	200L	250L	300L	400L
Temp. Range	0~65°C				
Temp. Fluctuation	±1 °C				
Temp. Stability/ Uniformity	±2 °C				
Humidity Range	50~90% RH (±5~8% RH)				
Sterilization Type	UV lamp				
Shelves	3pcs/adjustable				
Consumption	300W	350W	430W	480W	750W
Power Supply	AC110/220V±10%, 50/60Hz				
Standard Accessory	Micro printer(for HTII series), humidifier				
Internal Size(W*D*H)mm	450*420*850	450*450*1000	480*490*1070	520*500*1170	580*540*1270
External Size(W*D*H)mm	590*620*1400	590*640*1550	620*680*1620	660*690*1720	720*740*1820
Gross Weight(kg)	120	138	147	157	170

Didac Scientific Pvt. Ltd,
Martinfield Business Centre, 108 Martinfield, Welwyn Garden City , United Kingdom
Direct Contact Details sales@didacscientific.co.uk
www.didacscientific.co.uk/